### The Catalina Sky Survey: Challenges of Running a NEA Survey

#### Eric J. Christensen

A. R. Gibbs, A. D. Grauer, R. E. Hill, J. A. Johnson, R. A. Kowalski, S. M. Larson, F. C. Shelly







Equipment

Software

Survey Strategy

- Equipment
  - Telescopes, cameras, computers
- Software

Survey Strategy

- Equipment
  - Telescopes, cameras, computers
- Software
  - Automated acquisition and reduction pipelines
- Survey Strategy

- Equipment
  - Telescopes, cameras, computers
- Software
  - Automated acquisition and reduction pipelines
- Survey Strategy
  - Where to look, how long, how many revisits
- People

- Equipment
  - Telescopes, cameras, computers
- Software
  - Automated acquisition and reduction pipelines
- Survey Strategy
  - Where to look, how long, how many revisits
- People
  - Engineers, developers, observers



- Most NEO survey work is done by 1-m to 2-m class wide-field telescopes
- ALL current and past NEO survey telescopes were initially designed to do something else, or have competing science goals that can compromise the effectiveness of the NEO survey
- NEO survey efficiency benefits if everything can be optimized toward the single goal of discovery

#### Telescope

Primary metric is aperture, but optical design,
 f/ratio also matter

#### Camera

 Primary metric is FOV, but pixel scale, fill factor, readout speed, read noise also matter

#### Computers

- Telescope control, camera control, data processing
  - all need to be smoothly integrated

• Survey power: *étendue* 

$$A\Omega = Area * FOV$$

Area = collecting area, in  $m^2$ 

 $FOV = Field of view, in <math>\overline{deg^2}$ 

• Survey power: ndue

$$A\Omega = A$$
 \* FOV

Area = collect area, in FOV = Field or view, in deg-

Survey power: modified étendue

ME = Area \* FOV \* FF \* T \* OS

Area = collecting area, in m<sup>2</sup>
FOV = Field of view, in deg<sup>2</sup>
FF = Fill Factor of the focal plane array
T = Optical throughput
OS = Open Shutter efficiency (data throughput)

Still doesn't account for survey strategy, cadence choices, limiting magnitude, NEO population characteristics....


Try to maximize all inputs to this equation!

- When adapting an existing telescope for survey use, modification of collecting area or FOV may be difficult or expensive
- Fill factor is especially important when multiple detections of an object are needed – baseline detection efficiency scales with FF to the n<sup>th</sup> power, where n is the minimum number of visits for detection
- Example: 85% fill factor, 4 visits required for detection yields an efficiency of 0.85<sup>4</sup>, or 52.2%

- Throughput (optical throughput)
  - Can be estimated from number of mirrors, no. of transmissive optics, no. of AR coatings, CCD QE, filter characteristics

#### Examples:

- LSST 8.4-m: 3 mirrors, 3 correcting optics, 1 filter,
   9 AR coatings = ~15% throughput
- CSS 1.5-m: 1 mirror, 3 correcting optics, no filter,
   7 AR coatings = ~75% throughput



- Software is critical for any large-scale survey
- Data acquisition must be maximized (overheads minimized) – tight interfaces between telescope, camera + computers
- Large volumes of data must be processed quickly and reliably
- Must be maintainable and upgradable
- Steal what you can, write what you must


- CSS has "stolen" general-purpose building blocks:
  - Source extraction software (SExtractor)
  - Image display software (SAO ds9)
  - Astrometry (imwcs, SCAMP)
  - Orbit calculation software (find\_orb)
  - FITS manipulation routines (SAOTools)
- Don't reinvent the wheel!

- CSS has written NEO survey-specific elements:
  - Moving object detection software (con4)
  - Graphical user interface for acquisition and validation
  - Survey scheduling software
  - Image calibration software
  - Lots of scripting "glue" to stick the pieces together

#### Acquisition pipeline:


- For survey work, a tight integration between the TCS and camera is necessary
- Main job is to sequence telescope, camera and shutter. Tasks must be interleaved to eliminate unnecessary overhead, e.g. telescope must slew while camera reads out
- Other tasks may include calculating and applying focus adjustments, capturing telemetry to write to FITS header, fetching next coordinates, monitoring weather conditions
- Minimize time not spent doing something critical.
   Fractions of a second per imaging cycle can matter!

- Reduction pipeline
  - Involves familiar image reduction tasks (bias, flat, source extraction, astrometry, photometric calibration)
  - Must run quickly and reliably without human intervention, due to large data volume
  - Moving object detection software, e.g. MOPS, con4
  - Remember NEO discovery is the goal: can accept some amount of imperfect calibration as long as primary goal is met (NEOs are detected)



- So you have your survey system...what are you going to do with it?
- What are the characteristics of the NEO population you're interested in? Projection on sky, magnitude distribution, rates, known vs. unknown
- What are the strengths and weaknesses of other operational survey systems? Is there a niche to be filled? Where can you make the most impact?
- Considerations: exposure time, number of revisits, where to point (e.g. ecliptic, opposition, sweet spots)

- Coverage vs. Limiting Magnitude
  - Exposure time how faint, when do trailing losses become a problem?
  - How many revisits for moving object detection?



#### Real-time concerns


- NEOs move quickly! Depending on rate, they must be followed up within 2 - 24 hours else positional uncertainties can become too large for efficient recovery
- This drives pipelines and operational procedures toward real-time detection and reporting
- Critical for unusual events, e.g. 2008 TC<sub>3</sub> and 2014 AA,
   ~3-m asteroids discovered <24 hours before impact</li>
- Everything begins with discovery: risk assessment, physical characterization opportunities, etc. Get a solid initial orbit as soon as possible

- CSS baseline survey strategies:
  - 0.7-m Schmidt w/ 8.2 deg<sup>2</sup> FOV, V<sub>lim</sub>~19.7 : all sky, bias toward ecliptic
  - 1.5-m reflector w/ 1.2 deg<sup>2</sup> FOV,  $V_{lim}$ ~21.3 : +/- 5 deg. from ecliptic, bias toward opposition + sweet spots
  - 0.5-m Schmidt w/ 4.0 deg<sup>2</sup> FOV in S. Hemisphere,  $V_{lim}$ ~19.4 (now retired) : *all sky south of -30 Dec*
- 4 visits per night, total baseline 30-45 min.
- Revisit rates > 3-5 days

- Follow-up is an integral part of discovery
- Dedicated NEO follow-up capabilities exist.
   Typically new discoveries brighter than V~20 are followed up by amateur sites
- Fainter discoveries may need targeted followup, even if it means re-tasking your survey telescope to do the job




- Skilled observers can help maximize sensitivity and efficiency of the survey system
- At CSS, the fact that all NEO candidates are visually validated allows an extremely low detection threshold (S/N~1.2) and ensures a pure data stream



 Software for people vs. software for machines: people require specialized interfaces and visual

feedback





- Challenges of incorporating people:
  - People may make different decisions at different times, and different people may make different decisions given the same inputs (non-repeatable)
  - People need to eat, sleep, socialize, get paid
- Don't require people to do things that machines can do better (and vice versa)
- An ideal survey system fuses the best of human intelligence and adaptability, with the computational power of machines

### **Optimization**

- Optimization is a constant task!
  - Telescope / camera system: maximize optical throughput. Collimation / image quality requires maintenance
  - Computing power increases with time how can that work to your advantage?
  - Revisit fundamental assumptions often. Be prepared to modify survey cadence as our knowledge of the NEO population evolves, or as other survey assets evolve



### Any further questions, please contact me!

#### Eric Christensen

Catalina Sky Survey
Lunar and Planetary Laboratory
The University of Arizona

eric@LPL.arizona.edu





